

# Flexible thin layer open electrochemical cell

Publication number: JP2000502206 (T)

Publication date: 2000-02-22

Inventor(s):

Applicant(s):

Classification:

- International:

A61B5/00; A61N1/30; B65D51/24; H01M10/02; H01M10/04;  
H01M10/10; H01M10/12; H01M10/26; H01M10/30; H01M2/02;  
H01M2/16; H01M2/20; H01M2/30; H01M4/06; H01M4/12;  
H01M4/20; H01M4/26; H01M4/62; H01M4/66; H01M6/06;  
H01M6/12; H01M6/18; H01M6/22; H01M6/40; H01M6/42;  
H01M6/44; H01M6/46; A61B5/00; A61N1/30; B65D51/24;  
H01M10/02; H01M10/04; H01M10/06; H01M10/24; H01M2/02;  
H01M2/16; H01M2/20; H01M2/30; H01M4/06; H01M4/16;  
H01M4/26; H01M4/62; H01M4/66; H01M6/06; H01M6/12;  
H01M6/18; H01M6/40; H01M4/02; H01M6/42; (IPC1-  
7); H01M10/10; H01M6/22

- European:

A61B5/00R; A61N1/30; B65D51/24K; H01M10/04F;  
H01M10/12F2; H01M2/02E; H01M2/02E2; H01M6/12;  
H01M6/18B; H01M6/22; H01M6/40; Y02E60/12D

Application number: JP19960522621T 19961129

Priority number(s): WO1996US19048 19961129; US19950575180 19951220

Also published as:

US5811204 (A)

US5897522 (A)

US5852043 (A)

WO9722466 (A1)


TR9801149 (T2)

more >>

Abstract not available for JP 2000502206 (T)

Abstract of corresponding document: US 5811204 (A)

A flexible thin layer open liquid state electrochemical cell which can be used as a primary or rechargeable power supply for various miniaturized and portable electrically powered devices of compact design. The cell includes a wet electrolyte, yet maintains a flexible, thin and open configuration, thus devoid of accumulation of gases upon storage. The cell comprising a first layer of insoluble negative pole, a second layer of insoluble positive pole and a third layer of aqueous electrolyte, the third layer being disposed between the first and second layers and including a deliquescent material for keeping the open cell wet at all times; an electroactive soluble material for obtaining required ionic conductivity; and, a watersoluble polymer for obtaining a required viscosity for adhering the first and second layers to the third layer. The electrochemical cell of the present invention is preferably produced using a suitable printing technology.



Data supplied from the *espacenet* database — Worldwide